

Teeth Recognition for Person Identification

Rajiv Kumar

Department of Faculty of Computing

Botho University

Gaborone, Botswana

dhiman.rajiv@gmail.com

Abstract— In this research work, a model of teeth recognition has been proposed to identify a person. The persons' teeth image have been matched against the database of teeth images. An algorithm has been developed to recognize the teeth image by using the image processing methods. The author has been set a similarity criterion to match the teeth image against the image database by specifying the threshold value. This similarity criterion is used to identify a person. The labial teeth and gingiva photographic image database (LTG-IDB) have been taken to verify the results. The database consists 90 photographic images from 27 subjects. . The experiment results has carried on 20 teeth images of same person and 50 teeth images of different persons. MATLAB has been used for this purpose.

Keywords— Teeth image; Image processing; morphological operations; LTF-IDB database; MATLAB

I. INTRODUCTION

The author has been introduced a new approach to recognize the teeth of people. A set of teeth images have been used as template and saved in the image database. Most biometric methods use a single image to identify a person. These processes are complex and need sophisticated equipment and a controlled environment to be correctly used. It is almost impossible to fulfill these conditions to recognize the teeth [3] [8] [9]. Author has been taken the RGB image of teeth of persons. The RGB image has been converted into the gray-scale image. The gray-scale image is converted into image of size 20×20 by applying the resize operation. Author has recognized the pattern of teeth and converted the image into binary image by applying the threshold value [1]. The binary image has cropped into smaller size and number of one's has been counted present in the pattern [4] [5]. Then, the teeth image has fetched from the image database and match with the existing teeth image [3]. Author has been derived the similarity criteria. If similarity measure between these two teeth image is above threshold value, then the image belongs to the same person, otherwise, not [2] [6] [7]. MATLAB has been used to implement the algorithm [10].

The paper is organized as: author has proposed the model in section II. The results analysis have been performed in section III. Finally, section IV conclude the paper.

II. PROPOSED MODEL OF TEETH RECOGNITION

The block diagram of proposed model is shown in fig. 1:




Fig. 1. Block diagram of teeth recognition

A. Methodology

1. Read the original RGB image.
2. Resize the RGB image into size 256×256 .
3. Convert the RGB image into gray-scale image.
4. Resize the image into size 20×20 .
5. Convert gray-scale image into binary image by choosing threshold value.
6. Crop the binary image.
7. Count the number of one's.
8. Take another RGB image and repeat step from 1 to 7.
9. Calculate the percentage difference between these two images.

$$Difference = \left| \frac{Image_1 - Image_2}{(Image_1 + Image_2)/2} \right| \times 100 \quad (1)$$

10. Find the similarity between these two images

$$Similarity = 100 - Difference \quad (2)$$

11. Choose a threshold value.
12. If $Similarity \geq Threshold$, then images belongs to same person otherwise they belong to different persons.
13. End.

B. Working of the proposed model

The following steps are:

1. Take RGB Image of teeth 1 as shown in fig. 2:




match against the similarity criteria. If they are more than specified threshold value, then they belong to the same person. The threshold value is 74. The experiment results prove that the accuracy of the proposed model is found more than 90%.

TABLE I. TEETH IMAGE OF SAME PERSON

S No	Same person		Similarity (%)
1	Image-1	Image-2	61
2	Image-1	Image-3	74
3	Image-1	Image-4	74
4	Image-1	Image-5	84
5	Image-2	Image-3	85
6	Image-2	Image-4	86
7	Image-2	Image-5	76
8	Image-3	Image-4	99
9	Image-3	Image-5	90
10	Image-4	Image-5	89

The similarity between two teeth of same person has been shown in fig. 10:



In table II, authors have taken two set of teeth images belong to different persons. The experiment results show that the teeth images of different persons match only in case of 20%. The accuracy of the system is more than 80% in this case.

TABLE II. TEETH IMAGE OF DIFFERENT PERSON

SN	Different Persons		Similarity (%)
1	Image-11	Image-12	74
2	Image-11	Image-13	27
3	Image-11	Image-14	1
4	Image-11	Image-15	45
5	Image-11	Image-16	20
6	Image-12	Image-13	50
7	Image-12	Image-14	22
8	Image-12	Image-15	69
9	Image-12	Image-16	42

SN	Different Persons		Similarity (%)
11	Image-2	Image-15	51
12	Image-2	Image-16	25
13	Image-3	Image-11	79
14	Image-3	Image-14	18
15	Image-3	Image-15	65
16	Image-3	Image-16	38
17	Image-4	Image-11	79
18	Image-4	Image-12	94
19	Image-4	Image-13	45

10	Image-13	Image-14	68
----	----------	----------	----

20	Image-4	Image-14	17
----	---------	----------	----

The similarity between two teeth of different person has shown in fig. 11 and 12:




Fig. 11. Similarity among different set of teeth




Fig. 12. Similarity among different set of teeth

IV. CONCLUSION

In this paper, the model of teeth recognition for person identification has been proposed. The image processing techniques have been used to match the pattern of teeth image against the teeth image database (LTG-IDB). If the similarity between two teeth images is above the specified threshold value, then they belong to the same person otherwise they belong to different persons. The author concluded that the accuracy of the proposed system is more than 90% when the teeth images belong to same person. The proposed system is

80% accurate when the teeth images belong to different persons. In short, the conclusion is that the accuracy of the proposed system is more than 85% on the given set of teeth images.

ACKNOWLEDGMENT

The author is grateful to the Management, the Dean, the HOD and all staff members of Faculty of Computing department, Botho University, Gaborone, Botswana for their valuable support.

REFERENCES

- [1] Armangue, X., Salvi, J., "Overall view regarding fundamental matrix estimation". *Image and Vision Computing*, pp. 205-220, 2003.
- [2] Chih-Hong Kao, Sheng-Ping Hsieh and Chih-Cheng Peng, "Study of Feature-Based Image Capturing and Recognition Algorithm", 'International Conference on Control, Automation and Systems' 2010, pp. 1855-1861.
- [3] Eckhard et al.; Labial teeth and gingiva color image segmentation for gingival health-state assessment; IS&T/ 6th European Conference on Color in Graphics, Imaging and Vision, CGIV 2012, pp. 102-107, Amsterdam (Netherlands).
- [4] Forsyth D. A., Ponce, J., "Computer Vision: a Modern Approach", 1st Ed., Prentice Hall, 1998. 693p.
- [5] Gonzalez RC, Woods RE. *Digital Image Processing Using MATLAB*. New Jersey, USA: Pearson, Prentice-Hall, Pearson Education, Inc. 2004.
- [6] Rafael C., Gonzalez and Richard E., Wood, *Digital Image Processing*, 2nd Edition.
- [7] S Sapna Varshney, Navin Rajpal and Ravindar Purwar, "Comparative Study of Image Segmentation Techniques and Object Matching using Segmentation", *International Conference on Methods and Models in Computer Science*, 2009.
- [8] Wang Haihui, Wang Yanli, Zhao Tongzhou, Wang Miao, Wu Mingpeng, "Images Segmentation Method on Comparison of Feature Extraction Techniques", *IEEE* 2010.
- [9] Xitao Zheng, Yongwei Zhang, Qian Song, and Hong Ding, "A New Approach on Teeth Image Recognition", 'Proceedings of the 2010 International Conference on Image Processing, Computer Vision, & Pattern Recognition', 2010, PP 769-773.
- [10] Online Available: <http://www.mathworks.com/products/matlab/>.